

D812



USB port



Expansion
module
connectable



HD audio



Anti-bacterial
housing



SmartLabel



Security (TLS
& SRTP)



OpenVPN

The perfect everyday companion

The Snom D812 is another entry-level device in Snom's professional D8xx series. Equipped with a large display, it offers a unique quality in its price segment. The 8 freely programmable SmartLabel keys allow individual adaptation to the needs of the user - be it for setting up call groups, speed dials or similar functions. With its

modern technology, excellent voice quality and elegant design, the D812 offers everything that is required for contemporary office communication - and all at an extremely attractive price. Welcome to the world of professional IP telephony with the Snom D812!

Basics

- Product information
 - IP desk phone D812 | gunmetal black | PN 00004690
 - Anti-bacterial housing
 - Operating system: Linux
- Placement
 - Indoor, desktop, wall mounting¹

Dimensions and weight

- Dimensions (L × W × H, approx.)
 - 210 mm × 243 mm × 45 mm without footstand
 - 193 mm × 243 mm × 165 mm with footstand
- Weight (approx.)
 - 1.12 kg with footstand

Display and indicators

- Display
 - TFT liquid crystal display (LCD): IPS panel, true colour, backlit
 - Size (diagonal): 5.0" (127 mm)
 - Size (W × H): 110 mm × 62 mm
 - Resolution: 480 × 272 pixel
- 13 LED indicators
 - Call status indication: 1 red LED
 - Message waiting indication (MWI): 1 red LED
 - Function key status indication: 8 multicolour LEDs
 - Audio key status indication: 3 LEDs (1 red / 2 green)

Keypad and function keys

- 39 hard keys in total
 - 12 keys (standard ITU telephone keypad)
 - 5-way navigation key
 - 4 context-sensitive function keys
 - Programmable function keys:
 - 8 SmartLabel keys (with multicolour LED)

- Key mapping of up to 32 functions (8 keys × 4 pages)
- 5 dedicated audio keys
 - Mute (with red LED)
 - Speakerphone (with green LED)
 - Headset (with green LED)
 - Volume + / - (rocker)
- 5 dedicated function keys
 - Cancel
 - Message (with red LED)
 - Transfer
 - Hold
 - Redial
- Keyboard lock
- Expansion module connection via USB port for up to 3 × D8C¹

Audio devices, codecs and features

- Casing microphone | Casing speaker
 - Frequency range: 100 Hz - 8.0 kHz
 - Speakerphone mode: Full duplex, HD audio, Acoustic Echo Cancellation (AEC)
- Corded handset: Microphone | Handset earpiece
 - Frequency range: 150 Hz - 8.0 kHz
 - Noise cancellation, HD audio, Hearing aid compatible (HAC)
- Audio codecs
 - G.711 (A-law, μ -law), G.722, G.723.1, G.726, G.729AB, GSM6.10(FR), Opus
- Dual-tone multi-frequency signalling (DTMF / RFC2833):
 - SIP-INFO, in-band, out-of-band
- Related features
 - Comfort Noise Generator (CNG)
 - Voice Activity Detection (VAD)
 - Audio response time
 - Adaptive jitter buffer
 - Packet loss concealment (PLC)

Interfaces and connections

- Power options
 - Power over Ethernet (PoE)
 - IEEE 802.3af, class 3 | IEEE 802.3az³
 - Power adapter¹
 - 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 2 A, 10 W¹
- Wired interfaces
 - Power adapter: coaxial power connector (socket)
 - Network connectivity: 2 × RJ45-8P8C sockets (*NET, PC*) → Gigabit Ethernet (GbE)
 - USB connectivity: USB 2.0 type A port
 - Corded handset: RJ9-4P4C socket
 - Headset: RJ9-4P4C socket
 - EHS adapter:¹ RJ12-6P6C socket
- Wireless interfaces
 - Third party headset support
 - DECT: optional via A230¹
 - Network connectivity: WLAN optional via A210¹
- Sensors
 - Hook switch sensor

User interfaces and setup

- Configuration and setup via menu-driven web user interface (WUI)
 - Password-protected login
 - Secure web server/client (HTTPS)
- Configuration and setup via menu-driven phone user interface (PUI)
- Automatic configuration via provisioning
 - Loading of settings and firmware via HTTP, HTTPS, TFTP

- Supported DHCP provisioning options 43 / 60 / 66 / 67
- Secure Redirection And Provisioning Service (SRAPS) support
- Remote management via TR-069 / TR-069 Annex G (TR-111) / TR-369
- Plug & Play (PnP) support
- Localization
 - Languages
 - Time zone, dial tone
- Diagnostic
 - SIP / PCAP trace
 - Syslog
- Related features
 - Dual firmware partition

Networking technologies and protocols

- Network technologies
 - OpenVPN, VLAN (IEEE 802.1q)
- VoIP related protocols and techniques
 - SIP, SDP, RTP, RTCP, RTCP-XR, SIP REFER method (RFC 3515), rport (RFC 3581), ENUM, ICE, STUN
- Secure VoIP protocols
 - SIPS (SIP over TLS), SRTP, SRTCP
- Network protocols
 - IPv4 / IPv6 (dual stack), DHCP, NTP, LDAP, LLDP-MED, HTTP, TFTP, L2TP
- Secure network protocols
 - TLS V1.2 HTTPS, IEEE 802.1X (EAPoL)
- Remote management protocols
 - TR-069, TR-069 Annex G (formerly TR-111), TR-369 (USP)

Directory support and call features

- 12 SIP identities / accounts
 - Up to 12 simultaneous calls
- Directory support
 - [LDAP \(server-based directory\)](#)
 - [Local directory with up to 2,000 entries](#)
- Outgoing call features
 - Speed dialling via function keys
 - Speed dialling
 - [URL dialling](#)
 - [Local dial plan](#)
 - Redial (via dialled calls list)
 - Automatic redial on busy
 - Caller identification (CLIP)
 - Calling Line Identification Restriction (CLIR)
 - [Call completion \(busy/unreachable\)²](#)
 - [Intercom](#)
 - [Multicast paging](#)
- Incoming call features
 - [Call waiting/swapping](#)
 - Auto answer
 - **Call barring / blocking:** deny list, anonymous calls, Do Not Disturb (DND) mode
 - [Call diversion](#)
 - [Call deflection](#)
- Connected call features
 - Mute microphone
 - Hold

- Music on hold²
- [Blind call transfer](#)
- [Attended call transfer](#)
- 2+1 (4+1) local conferencing³
- Call park / unpark²
- Client Matter Code (CMC)²
- Related features
 - Call history lists of missed, received, dialed, rejected, and deflected calls
 - [Extension monitoring \(Busy lamp field\), call pickup²](#)

Package contents

- Hardware
 - IP desk phone D812
 - Corded handset
 - Footstand
 - Ethernet cable: 1.5 m
- Documentation
 - [Quick Installation Guide](#)
 - [GNU General Public License](#)

Environmental conditions

- Operating ambient temperature:
 - 0 °C - +35 °C
- Nonoperating (storage) temperature:
 - -10 °C - +45 °C
- Humidity (non-condensing):
 - 5 % - 95 %

¹ Available separately

² If supported by PBX

³ Optional via software

Snom accessories and compatible devices

- PoE injector
 - A5E (PN 00004079)
- Power adapter
 - Snom 10W PSU (PN 00004570)
- Wall mount kit
 - D8xx WM (PN 00004544)
- Corded wideband handset
 - D8xx WB handset (PN 00004561)
- USB dongle
 - Wireless LAN: A210 (PN 00004384)
 - DECT: A230 (PN 00004386)
- EHS adapter
 - EHS Advanced 2.0 (PN 00002362)
- Wireless conference speakerphone (USB)
 - C300 (PN 00004584)
- DECT headset via RJ9+EHS / USB
 - A170C (PN 00004733)
- Wired headset via RJ9
 - Binaural: A310D (PN 00004626)
 - Monaural: A100M (PN 00004341), A310M (PN 00004624)
- Wired headset via USB
 - Binaural: A330D (PN 00004598)
 - Monaural: A330M (PN 00004597)
- BT headset via Bluetooth dongle
 - A350M (PN 00004658)
- Expansion module
 - D8C (PN 00004562)



A5E



10 W PSU



A210



A230



EHS 2.0



D8C



C300



A170C



A100M



A310M



A310D



A330M




A330D



A350M

Interoperability



Series overview



D810W



D812



D815W



D815WB



D862



D865



D892M



D8C

Disclaimer

Further information: [Snom D812 webpage](#) | [Snom Service Hub D812](#) | [Quick Installation Guide D812](#) | [User manual D812](#) | [Short User Manual D812](#) | [GNU General Public License](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.