

D815WB



Wi-Fi



Bluetooth



USB port



Expansion
module
connectable



Anti-bacterial
housing



HD audio



SmartLabel



Security (TLS
& SRTP)



OpenVPN

Stylish and powerful: the Snom D815WB

The Snom D815WB is an excellent option for everyday use in any office environment. With its elegant design, USB port, integrated Wi-Fi and a total of ten SmartLabel keys, it offers a wide range of possibilities. The outstanding feature of the D815WB is its large 5-inch display, which enables good presentation and clarity.

The audio quality meets the high standards that apply to all Snom IP devices. The Snom D815WB thus combines an elegant design and first-class performance at an unbeatable price.

Basics

- Product information
 - IP desk phone D815WB | gunmetal black → PN 00004727, EAN 4262377561294, UPC 810100351298 | white → PN 00004793, EAN 4262377562079, UPC 810100352073
 - Anti-bacterial housing
 - Operating system: Linux
- Placement
 - Indoor, desktop, wall mounting¹

Dimensions and weight

- Dimensions (L × W × H, approx.)
 - 210 mm × 243 mm × 45 mm without footstand
 - 193 mm × 243 mm × 165 mm with footstand
- Weight (approx.)
 - 1.12 kg with footstand

Display and indicators

- Display
 - TFT liquid crystal display (LCD): IPS panel, true colour, backlit
 - Size (diagonal): 5.0" (127 mm)
 - Size (W × H): 110 mm × 62 mm
 - Resolution: 480 × 272 pixel
- 15 LED indicators
 - Call status indication: 1 red LED
 - Message waiting indication (MWI): 1 red LED
 - Function key status indication: 10 multicolour LEDs

- Audio key status indication: 3 LEDs (1 red / 2 green)

Keypad and function keys

- 43 hard keys in total
 - 12 keys (standard ITU telephone keypad)
 - 5-way navigation key
 - 4 context-sensitive function keys
 - Programmable function keys
 - 10 SmartLabel keys (with multicolour LED)
 - Key mapping of up to 40 functions (10 keys × 4 pages)
- 5 dedicated audio keys
 - Mute (with red LED)
 - Speakerphone (with green LED)
 - Headset (with green LED)
 - Volume + / - (rocker)
- 7 dedicated function keys
 - Cancel
 - Message (with red LED)
 - Directory
 - Transfer
 - Hold
 - Conference
 - Redial
- Keyboard lock
- Expansion module connection via USB port for up to 3 × D8C¹

Audio devices, codecs and features

- Casing microphone | Casing speaker
 - Frequency range: 100 Hz - 8.0 kHz
 - Speakerphone mode: Full duplex, HD audio, Acoustic Echo Cancellation (AEC)
- Corded handset:
 - Microphone | Handset earpiece
 - Frequency range: 150 Hz - 8.0 kHz
 - Noise cancellation, HD audio, Hearing aid compatible (HAC)
- Audio codecs
 - G.711 (A-law, μ -law), G.722, G.723.1, G.726, G.729AB, GSM6.10(FR), Opus
- Dual-tone multi-frequency signalling (DTMF / RFC2833):
 - SIP-INFO, in-band, out-of-band
- Related features
 - Comfort Noise Generator (CNG)
 - Voice Activity Detection (VAD)
 - Audio response time
 - Adaptive jitter buffer
 - Packet loss concealment (PLC)

Interfaces and connections

- Power options
 - [Power over Ethernet \(PoE\)](#)
 - IEEE 802.3af, class 3 | IEEE 802.3az³
 - Power adapter¹
 - 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 2 A, 10 W¹
- Wired interfaces
 - Power adapter: coaxial power connector (socket)
 - Network connectivity: 2 × RJ45-8P8C sockets (*NET, PC*) → Gigabit Ethernet (GbE)
 - USB connectivity: 1 × USB 2.0 type A ports

- Corded handset: RJ9-4P4C socket
- Headset: RJ9-4P4C socket
- [EHS adapter](#):¹ RJ12-6P6C socket
- Wireless interfaces
 - Network connectivity: WiFi
 - [Headset connectivity: Bluetooth](#)
- Sensors
 - Hook switch sensor

User interfaces and setup

- [Configuration and setup via menu-driven web user interface \(WUI\)](#)
 - Password-protected login
 - Secure web server/client (HTTPS)
- [Configuration and setup via menu-driven phone user interface \(PUI\)](#)
- [Automatic configuration via provisioning](#)
 - Loading of settings and firmware via HTTP, HTTPS, TFTP
 - Supported DHCP provisioning options 43 / 60 / 66 / 67
 - [Secure Redirection And Provisioning Service \(SRAPS\) support](#)
 - [Remote management via TR-069 / TR-069 Annex G \(TR-111\) / TR-369](#)
 - Plug & Play (PnP) support
- Localisation
 - [Languages](#)
 - Time zone, dial tone
- Diagnostic
 - SIP / PCAP trace
 - Syslog
- Related features
 - Local call recording via USB
 - Dual firmware partition

Networking technologies and protocols

- Network technologies
 - OpenVPN, VLAN (IEEE 802.1q)
 - WiFi: IEEE 802.11n (Wi-Fi 4), IEEE 802.11ac (Wi-Fi 5)
- VoIP related protocols and techniques
 - SIP, SDP, RTP, RTCP, RTCP-XR, SIP REFER method (RFC 3515), rport (RFC 3581), ENUM, ICE, STUN
- Secure VoIP protocols
 - SIPS (SIP over TLS), SRTP, SRTCP
- Network protocols
 - IPv4 / IPv6 (dual stack), DHCP, NTP, LDAP, LLDP-MED, HTTP, TFTP, L2TP
- Secure network protocols
 - TLS V1.3, HTTPS, IEEE 802.1X (EAPoL)
- Remote management protocols
 - TR-069, TR-069 Annex G (formerly TR-111), TR-369 (USP)

Directory support and call features

- 12 SIP identities / accounts
 - Up to 12 simultaneous calls
- Directory support
 - LDAP (server-based directory)
 - Local directory with up to 2,000 entries
- Outgoing call features
 - Speed dialling via function keys
 - URL dialling
 - Local dial plan
 - Redial (via dialled calls list)
 - Automatic redial on busy
 - Caller identification (CLIP)
 - Calling Line Identification Restriction (CLIR)
 - Call completion (busy/unreachable)²
 - Intercom
 - Multicast paging

- Incoming call features
 - Call waiting/swapping
 - Auto answer
 - **Call barring / blocking:** deny list, anonymous calls, Do Not Disturb (DND) mode
 - Call diversion
 - Call deflection
- Connected call features
 - Mute microphone
 - Hold
 - Music on hold²
 - Blind call transfer
 - Attended call transfer
 - 2+1 (4+1) local conferencing³
 - Call park / unpark²
 - Client Matter Code (CMC)²
- Related features
 - Call history lists of missed, received, dialed, rejected, and deflected calls
 - Extension monitoring (Busy lamp field), call pickup²

Package contents

- Hardware
 - IP desk phone D815WB
 - Corded handset
 - Footstand
 - Ethernet cable: 1.5 m
- Documentation
 - **Safety instructions**

Environmental conditions

- Operating ambient temperature:
 - 0 °C - +35 °C
- Nonoperating (storage) temperature:
 - -10 °C - +45 °C
- Humidity (non-condensing):
 - 5 % - 95 %

Snom accessories

- Power adapter Snom 10W PSU (PN 00004570)
- PoE injector A5E (PN 00004079)
- **Wall mount kit** D8xx WMK-M (PN 00004544)
- Corded wideband handset D8xx WB handset (PN 00004561)



- DECT headset via RJ9 + EHS / USB A170C (PN 00004733)
- Wired headset via RJ9
 - Monaural: A100M (PN 00004341)
 - Monaural: A310M (PN 00004624)
 - Binaural: A310D (PN 00004626)



Compatible Snom devices

- Expansion module D8C (PN 00004562, PN 00004794)
- EHS adapter EHS Advanced 2.0 (PN 00002362)
- USB dongle
 - DECT: A230 (PN 00004386)
 - Bluetooth: A220 (PN 00004648)



- Wired headset via USB
 - Monaural: A330M (PN 00004597)
 - Binaural: A330D (PN 00004598)
- BT headset via integrated Bluetooth
 - Monaural: A350M (PN 00004658)
 - Binaural: A350D (PN 00004795)
- Wireless conference speakerphone (USB) C300 (PN 00004584)



Series overview



D8C

D810W

D812

D815W

D815WB

D862

D865

D892M

D895M

Interoperability



¹ Available separately

² If supported by PBX

³ Optional via software

Disclaimer

Further information: [D815WB webpage](#) | [Snom Service Hub D815WB](#) | [Safety instructions D815WB](#) | [Short User Manual D815WB](#) | [General Public License \(GNU\)](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.