

D892M



DECT handset



Wi-Fi



Bluetooth



USB port



Anti-bacterial housing



Expansion module connectable



HD audio



SmartLabel



Security (TLS & SRTP)



OpenVPN

Premium IP Desk Phone with integrated DECT Mobility

The Snom D892M builds on the D8xx legacy as a true all-rounder, now with a built-in DECT receiver for up to 50m wireless mobility and a cleaner desk. Ten SmartLabel keys with LED backlighting offer flexible customisation. Its 40° adjustable LCD ensures vibrant colours and readability in any light. With integrated

Bluetooth, Wi-Fi, and hearing aid compatibility, the D892M is a connectivity powerhouse. Designed for professionals handling high call volumes and complex IT environments, it's a future-ready desk phone combining usability with cutting-edge wireless tech.

Basics

- Product information
 - IP desk phone D892M + DECT handset
D8M | gunmetal black | PN 00004539, EAN
4260059583299, UPC 811819013293
 - Contactless charging
 - Operating system: Linux
 - Anti-bacterial housing
- Placement
 - Indoor, desktop, wall mounting¹

Dimensions and weight

- Dimensions (L × W × H, approx.)
 - 210 mm × 243 mm × 45 mm without footstand
 - 193 mm × 243 mm × 165 mm with footstand
- Weight (approx.)
 - 1.12 kg with footstand

Display and indicators

- Display
 - TFT liquid crystal display (LCD): tiltable, IPS panel, true colour, backlit
 - Size (diagonal): 5.0" (127 mm)
 - Size (W × H): 110 mm × 62 mm
 - Resolution: 1,280 × 720 pixels
- IP desk phone: 15 LED indicators
 - Call status indication: 1 red LED
 - Message waiting indication (MWI): 1 red LED
 - Function key status indication: 10 multicolour LEDs
 - Audio key status indication: 3 LEDs (1 red / 2 green)
- DECT handset: 1 LED indicator
 - Charging indication: 1 multicolour LED

Keypad and function keys

- IP desk phone: 43 hard keys in total
 - 12 keys (standard ITU telephone keypad)
 - 5-way navigation key
 - 4 context-sensitive function keys
 - Programmable function keys
 - 10 SmartLabel keys (with multicolour LED)
 - Key mapping of up to 40 functions (10 keys × 4 pages)
 - 5 dedicated audio keys
 - Mute (with red LED)
 - Speakerphone (with green LED)
 - Headset (with green LED)
 - Volume + / -
 - 7 dedicated function keys
 - Cancel
 - Message (with red LED)
 - Directory
 - Transfer
 - Hold
 - Conference
 - Redial
- DECT handset: 5 hard keys in total
 - 3 dedicated audio keys
 - Volume + / -
 - Mute / Unmute
 - 2 dedicated function keys
 - Onhook / offhook
 - Power on / off
- Related features
 - Keyboard lock
 - Expansion module connection via USB port for up to 3 × D8C¹

Audio devices, codecs and features

- IP desk phone: Casing microphone | Casing speaker
 - 2 dedicated microphones
 - Frequency range: 100 Hz - 14.0 kHz
 - Speakerphone mode: Full duplex, HD audio
 - Speakerphone RMS power: 5 W
- DECT handset: Microphone | Handset earpiece
 - Noise cancellation, HD audio
 - Frequency range: 150 Hz - 8.0 kHz
 - Hearing aid compatible (HAC)
- Audio codecs: G.711 (A-law, μ -law), G.722, G.723.1, G.726, G.729, Opus
- Dual-tone multi-frequency signalling (DTMF / RFC2833): SIP-INFO, in-band, out-of-band
- Related features
 - Comfort Noise Generator (CNG)
 - Voice Activity Detection (VAD)
 - Audio response time
 - Adaptive jitter buffer
 - Packet loss concealment (PLC)

Interfaces and connections

- Power options: IP desk phone
 - **Power over Ethernet (PoE):** IEEE 802.3af, class 3 | IEEE 802.3az³
 - Power adapter:¹ 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 3 A, 15 W
- Power options: DECT handset
 - Battery: 850 mAh, lithium-ion, non-removable, rechargeable, up to 12 h wideband talk time, up to 200 h standby time, up to 8 h charging time
- Wired interfaces
 - Power adapter: coaxial power connector (socket)
 - Network connectivity: 2 × RJ45-8P8C sockets (NET / PC) → Gigabit Ethernet (GbE)
 - USB connectivity: 2 × USB 2.0 type A ports

- Corded handset:¹ RJ9-4P4C socket
- Headset:¹ RJ9-4P4C socket
- **EHS adapter:**¹ RJ12-6P6C socket
- Wireless interfaces
 - DECT handset: DECT
 - Network connectivity: WiFi
 - **Headset connectivity:** Bluetooth
- Sensors
 - Hook switch sensor

User interfaces and setup

- **Configuration and setup via menu-driven web user interface (WUI)**
 - Visual and functional UX based re-design (phone manager)
 - Password-protected login
 - Secure web server/client (HTTPS)
- **Configuration and setup via menu-driven phone user interface (PUI)**
- **Automatic configuration via provisioning**
 - Loading of settings and firmware via HTTP, HTTPS, TFTP
 - Supported DHCP provisioning options 43 / 60 / 66 / 67
 - **Secure Redirection And Provisioning Service (SRAPS) support**
 - **Remote management via TR-069 / TR-069 Annex G (TR-111) / TR-369**
 - Plug & Play (PnP) support
- Localisation: Time zone, dial tone, **Languages**
- Diagnostic
 - SIP / PCAP trace
 - Syslog
- Related features
 - Local call recording via USB
 - Dual firmware partition

Networking technologies and protocols

- WiFi
 - Frequency band (2G): 2,400.0 - 2,483.5 MHz
 - IEEE 802.11b (Wi-Fi 2): up to 11 Mbps
 - IEEE 802.11g (Wi-Fi 3): up to 54 Mbps
 - IEEE 802.11n (Wi-Fi 4): up to 150 Mbps
 - Frequency band (5G): 5,150 - 5,350 MHz and 5,470 - 5,725 MHz
 - IEEE 802.11a (Wi-Fi 1): up to 54 Mbps
 - IEEE 802.11n (Wi-Fi 4) up to 150 Mbps
 - IEEE 802.11ac (Wi-Fi 5) up to 433 Mbps
- Network technologies
 - [OpenVPN](#), [VLAN \(IEEE 802.1q\)](#)
 - Bluetooth: BT 5.0, class 2
- VoIP related protocols and techniques
 - [SIP](#), [SDP](#), [RTP](#), [RTCP](#), RTCP-XR, SIP REFER method (RFC 3515), rport (RFC 3581), [ENUM](#), [ICE](#), [STUN](#)
- Secure VoIP protocols
 - [SIPS \(SIP over TLS\)](#), [SRTP](#), [SRTCP](#)
- Network protocols
 - IPv4 / IPv6 (dual stack), [DHCP](#), [NTP](#), [LDAP](#), [LLDP-MED](#), [HTTP](#), [TFTP](#), [L2TP](#)
- Secure network protocols
 - [TLS V1.3](#) incl. ciphers (forward secret & authenticated), [HTTPS](#), [IEEE 802.1X \(EAP-TLS - RFC 5216\)](#)
- Remote management protocols
 - [TR-069](#), [TR-069 Annex G \(formerly TR-111\)](#), [TR-369 \(USP\)](#)

Directory support and call features

- 12 SIP identities / accounts
 - Up to 12 simultaneous calls
- Directory support
 - [LDAP \(server-based directory\)](#)

- [Local directory with up to 50,000 entries](#)
- [Import/export phone book \(CSV, XML\)](#)
- [XML phonebook support](#)
- Outgoing call features
 - [Speed dialling via function keys](#)
 - [Speed dialling](#)
 - [URL dialling](#)
 - [Local dial plan](#)
 - [Redial \(via dialled calls list\)](#)
 - [Automatic redial on busy](#)
 - [Caller identification \(CLIP\)](#)
 - [Calling Line Identification Restriction \(CLIR\)](#)
 - [Call completion \(busy/unreachable\)²](#)
 - [Intercom](#)
 - [Multicast paging](#)
- Incoming call features
 - [Call waiting/swapping](#)
 - [Auto answer](#)
 - [Call diversion](#)
 - [Call barring / blocking](#): deny list, [dynamic central blacklist check²](#), anonymous calls, Do Not Disturb (DND) mode
- Connected call features
 - [Mute microphone](#)
 - [Hold](#)
 - [Music on hold²](#)
 - [Blind call transfer](#)
 - [Attended call transfer](#)
 - [5-way \(4+1\) local conferencing](#)
 - [Call park / unpark²](#)
 - [Client Matter Code \(CMC\)²](#)
- Related features
 - [Call history lists of missed, received, dialed, rejected, and deflected calls](#)
 - [Extension monitoring \(Busy lamp field\), call pickup²](#)

DECT technology and features

- Standard: DECT
- Frequency band
 - EU | UK | AU: 1,880 - 1,900 MHz
- RF transmission power
 - EU | UK | AU: < 250 mW
- Coverage
 - Up to 50 m indoor range

Package contents

- Hardware
 - IP desk phone D892M
 - DECT handset D8M
 - Metal pin (to switch power on/off)
 - Footstand
 - Ethernet cable: 1.5 m
- Documentation
 - **Safety instructions**

Environmental conditions

- Operating ambient temperature:
 - 0 °C - +35 °C
- Nonoperating (storage) temperature:
 - -10 °C - +45 °C
- Humidity (non-condensing):
 - 5 % - 95 %

Snom accessories

- Power adapter Snom 15W PSU (PN 00004715)
- PoE injector A5E (PN 00004679)
- **Wall mount kit** D8xx WMK-M (PN 00004544)
- Corded wideband handset D8xx-WB-HS (PN 00004561)



Compatible Snom devices

- Expansion module D8C (PN 00004562)
- EHS adapter EHS Advanced 2.0 (PN 00002362)
- DECT headset via USB / RJ9+EHS A170C (PN 00004733)
- BT headset via integrated Bluetooth
 - Monaural: A350M (PN 00004658)
 - Binaural: A350D (PN 00004795)
- Wired headset via RJ9
 - Monaural: A100M (PN 00004341)
 - Monaural: A310M (PN 00004624)
 - Binaural: A310D (PN 00004626)
- Wired headset via USB
 - Binaural: A330D (PN 00004598)
 - Monaural: A330M (PN 00004597)
- Wireless conference speakerphone (USB) C300 (PN 00004584)



Snom spare parts

- DECT handset D8M (PN 00004557)
- D865 / D892 black silkscreen generic (PN 00009117)



¹ Available separately

³ Optional via software

² If supported by PBX

Interoperability



Series overview



Disclaimer

Further information: [D892M webpage](#) | [Snom Service Hub D892M](#) | [Safety instructions D892M](#) | [Short User Manual D892M](#) | [Type approval](#) | [General Public License \(GNU\)](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.