

HD1





Hotel/hospitality features



DECT



HD audio



Anti-bacterial housing

Technical specification



Basics

- Product information
 - Cordless DECT handset | charging cradle | PN 00007002
 - Colour: gunmetal black
 - Anti-bacterial housing
 - Sturdy, solid construction
 - Ultra small footprint and compact design
- · Placement: indoor, desktop, nightstand

Dimensions and weight

- Dimensions (H x W x D, approx.)
 - Handset: 213 mm × 49 mm × 42 mm
 - Charging cradle: 71 mm × 96 mm × 108 mm
 - Handset (on the charging cradle, desk mounted): 71 mm × 115 mm × 214 mm
- Weight (approx.)
 - Handset: 178 g
 - Charging cradle: 285 g
 - Handset (on the charging cradle, desk mounted): 469 g

Indicators and keys

- 6 LED indicators
 - Charging cradle
 - Charging indication: 1 red LED
 - Handset
 - Flash/Talk key indication: 1 red LED
 - Mute status indication: 1 red LED
 - Speakerphone mode: 1 red LED
 - Hold status indication: 1 red LED
 - Low battery indication | Charging indication: 1 red LED
- Handset: 23 hard keys in total
 - 12 keys (standard ITU telephone keypad), backlit
 - 4 dedicated audio keys

 - MUTE [] Mute (with red LED)

- +VOLUME- | Volume + / (rocker)
- 2 programmable function keys
 - Speed dialling
- 5 dedicated function keys
 - TALK/FLASH [] Offhook (with red LED)
 - *EMERGENCY* [] Emergency
 - OFF 🛘 Onhook / Cancel
 - HOLD [] Hold (with red LED)
 - MESSAGES 🛘 Message

Audio devices and features

- Microphone
- Handset earpiece
 - Hearing aid compatible (HAC)
- Casing speaker
 - Speakerphone mode (via dedicated function key)

Interfaces and connections

- Power options
 - Handset: Battery (CORUN) AAA-NiMH 2.4 V,
 550 mAh, preinstalled, removable,
 rechargeable, up to 7 h talk time, up to 5 days
 standby time, up to 16 h charging time
 - Charging cradle: Power adapter (VT-PLII) 100 -240 V AC, 50/60 Hz, 150 mA | 6 V DC, 450 mA, 2.7 W
- Wired interfaces
 - Charging cradle: coaxial power connector (socket)
- Wireless interfaces
 - DECT



DECT technology and features

- Standard: DECT
 - Authentication/encryption of base and handset
 - · Wideband audio
- Frequency band
 - EU & UK & AU: 1,881.792 1,897.344 MHz
- Easy registration to compatible base stations (HD101)

Call features

- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Hold (via dedicated function key)
- Multicast paging
- Quick call answer (by simple pick-up from the base/charger)

Environmental conditions

- Operating ambient temperature: 5 °C 45 °C
- Humidity (non-condensing): 5 % 95 %

Package contents

- Hardware
 - DECT handset HD1
 - Battery: preinstalled
 - Charging cradle
 - Power adapter
- Documentation
 - Quick Installation Guide (QIG)

Snom accessories and compatible devices

- Guest room phone: HD101 (PN 00007001)
- Power adapter: Charging cradle HD1 PSU
 - EU: PN 00004683
 - UK: PN 00004684
 - AU: PN 00004685
- Battery HD1 (PN 00004509)

Series overview



HM201



HM₂



HD100



HD101

S T

HD1

HD350W

HD351W



HD3

Disclaimer

Further information: Snom HD1 website | Snom Service Hub | Type approval | Warranty information | Company locations

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.