

HD3









DECT handset



Customisable faceplate



Anti-bacterial housing



HD audio

Additional cordless DECT handset for HD31x/HD31xA with charging cradle

With the HD3 that is delivered with its own desk charging cradle, you can expand all HD3x1 and HD3x1A with up to 3 or 4 additional cordless handsets and thus offer your guests all the advantages in a larger space, as you can make calls in up to 5 locations/rooms. All handsets have the most important features for the

comfort of your guest: hands-free calling, muting and call hold! The HD3 has an antibacterial housing to protect against germs and is easy to clean. A large red LED indicator alerts the guest to calls or waiting messages. The handsets can be individually labeled.

Technical specification



Basics and equipment

- Product information
 - Cordless handset HD3 + Charging cradle | gunmetal black | PN 00007011
 - Sturdy, solid construction
 - Customisable section for colour or hotel branding¹
 - Anti-bacterial housing
- · Placement: Indoor, desktop, nightstand

Dimensions and weight

- Dimensions (H × W × D, approx.)
 - DECT handset: 48 mm × 21 mm × 203 mm
 - Charging cradle: 51 mm × 121 mm × 133 mm
 - DECT handset (on the charging cradle, desk mounted): 53 mm × 56 mm × 216 mm
- Weight (approx.)
 - DECT handset: 145 g
 - Charging cradle: 72 g
 - DECT handset (on the charging cradle, desk mounted): 344 g

Indicators and keys

- DECT handset: 5 LED indicators
 - Message waiting indication (MWI): 1 red LED
 - Flash/Talk key indication: 1 green LED
 - Speakerphone mode: 1 red LED
 - Mute status indication: 1 red LED
 - Low battery indication: 1 red LED
- Charging cradle: 1 LED indicator
 - Charging indication: 1 red LED
- DECT handset: 23 hard keys in total
 - 12 keys (standard ITU telephone keypad), backlit
 - 4 dedicated audio keys
 - Mute (with red LED)
- ¹ Available separately

- Speakerphone (with red LED)
- Volume +
- Volume -
- 3 programmable function keys
 - Speed dialling
- 4 dedicated function keys:
 - Offhook (with green LED)
 - Onhook
 - Message
 - Hold

Audio devices and features

- Microphone
- Handset earpiece
 - Hearing aid compatible (HAC)
- External speaker
 - Speakerphone mode
- Built-in assignable ringtones

Interfaces and connections

- Power options
 - DECT handset: Battery lithium-ion, 3.7 V,
 1,000 mAh, removable, rechargeable, up to 7 h
 talk time, up to 120 h standby time, up to 11 h
 charging time
 - Charging cradle: Power adapter (VT-PLII) 100 -240 V AC, 50/60 Hz, 150 mA | 6 V DC, 450 mA, 2.7 W
- Wired interfaces
 - Charging cradle: coaxial power connector (socket)
- Wireless interfaces
 - Handsets: DECT



DECT technology and features

- Standard: DECT
 - Wideband audio
- Frequency band
 - EU & UK & AU: 1,881.792 1,897.344 MHz
- Easy registration to compatible base stations

Call features

- Quick call answer (by simple pick-up from the base/charger)
- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Speakerphone mode (via dedicated function key)
- Hold (via dedicated function key)
- Multicast paging

Environmental conditions

- Operating ambient temperature:
 - 5 °C +45 °C
- Humidity (non-condensing):
 - 5% 95%

Package contents

- Hardware
 - DECT handset HD3
 - Battery
 - Charging cradle
 - Power adapter
- Documentation
 - Quick Installation Guide

Snom accessories and compatible devices

- Guest room phone:
 - HD331 (PN 00007034)
 - HD331A (PN 00007033)
 - HD341 (PN 00007042)
 - HD341A (PN 00007043)
 - HD351W (PN 00007009)
 - HD351A (PN 00007031)
- Battery HD3 (PN 00004627)
- Power adapter: HD3 PSU
 - EU: PN 00004683
 - UK: PN 00004684
 - AU: PN 00004685

Series overview







HD30L /



HD300 /



HD331 / HD331A



HD340 / HD340A



HD341 / HD341A



HD350W / HD350A



HD351W /

Disclaimer

Further information: Snom HD3 webpage | Snom Service Hub HD3 | Quick Installation Guide HD3 | User manual HD3 | Type approval | Warranty information | Company locations

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.