

# HD340



Hotel/hospitality  
features



Customisable  
faceplate



Anti-bacterial housing



Power over Ethernet  
(PoE)



HD audio

## The compact hotel and guest room telephone

The HD340 is the slim option for hotels and guest rooms, focusing on the essentials without sacrificing convenience. With just two rows of keys and a clear user interface, it offers all the essential functions: five speed dial buttons for hotel facilities, a speakerphone function, volume control, and mute. Thanks to the

interchangeable handset faceplate and custom-designed inserts, this slim desk phone blends seamlessly into any environment. GDPR-compliant by design: No storage of personal data such as dialed numbers!

## Basics and equipment

- Product information
  - IP Guest room phone HD340 + Corded handset | gunmetal black | PN 00007044
- Equipment
  - Anti-bacterial housing
  - Sturdy, solid construction
  - [Fully customisable faceplate for hotel branding and dialing instructions<sup>1</sup>](#)
- Placement: Indoor, desktop, nightstand, wall mounting

## Dimensions and weight

- Dimensions (H × W × D, approx.)
  - Corded handset (on the base cradle, desk mounted): 183 mm × 82 mm × 121 mm
  - Corded handset (on the base cradle, wall mounted): 216 mm × 82 mm × 61 mm
  - Packaging (1 × HD340): 214 mm × 152 mm × 110 mm
  - Packaging (12 × HD340): 234 mm × 480 mm × 460 mm
- Weight (approx.)
  - Corded handset (on the base cradle, desk mounted): 544 g
  - Corded handset (on the base cradle, wall mounted): 363 g
  - Packaging (12 × HD340): 11.23 kg

## Indicators and keys

- Telephone base: 3 LED indicators
  - Call status indication | Message waiting indication (MWI): 1 red LED
  - Mute status indication: 1 red LED
  - Speakerphone mode: 1 red LED
- Telephone base: 21 hard keys in total

- 12 keys (standard ITU telephone keypad)
- 4 dedicated audio keys
  - Speakerphone mode (with red LED)
  - *MUTE* → Mute (with red LED)
  - *VOL+* → Volume +
  - *VOL-* → Volume -
- 5 programmable function keys: Speed dialling

## Audio devices and features

- Telephone base
  - Casing microphone
  - Casing speaker
- Corded handset
  - Microphone
  - Handset earpiece
- Hearing aid compatible (HAC)
- Built-in assignable ringtones

## Interfaces and connections

- Power options
  - [Power over Ethernet \(PoE\): IEEE 802.3af, class 2](#)
  - Power adapter<sup>1</sup>
- Wired interfaces
  - Telephone base
    - Network connectivity: RJ45-8P8C socket → Gigabit Ethernet (GbE)
    - Handset cord: custom socket
  - Corded handset
    - Handset cord: custom socket

## Interoperability

- Interoperable with all major IP-PBX platforms

## Networking technologies and protocols

- VLAN support
- [SIP \(RFC 3261\)](#)

## Call features

- Speed dialling via function keys
- Mute microphone (via dedicated function key)

## Environmental conditions

- Operating ambient temperature
  - 5 °C - +45 °C
- Humidity (non-condensing)
  - 5 % - 95 %

## Package contents

- Hardware
  - Telephone base
  - Handset
  - Handset cord: 330 mm

- Footstand
- Wall mount kit
- 2 Ethernet cables: Cable length (approx.)  
140 mm | 2 m

- Documentation
  - [Safety instructions \(GPSR\)](#)
  - [GNU General Public License](#)

## Snom accessories and compatible devices

- PoE injector: [A5E \(PN 00004679\)](#)
- Power adapter
  - EU: Base PSU (PN 00004687)
  - UK: Base PSU (PN 00004688)
  - AU: Base PSU (PN 00004689)

## Series overview



<sup>1</sup> Available separately

## Disclaimer

[Further information: Snom HD340 webpage](#) | [Snom Service Hub HD340](#) | [Short User Manual HD340](#) | [Safety instructions HD340](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.