

# HD340A



Hotel/hospitality features



Customisable faceplate



Anti-bacterial housing

## Compact analogue telephone for hotels and guest rooms

Compact analogue telephone for hotels and guest rooms with intuitive operation, antibacterial casing and all important comfort-features: speed dial, speakerphone, volume control and mute. Interchangeable backplates

and flexible mounting options ensure perfect integration into any environment.

## Basics and equipment

- Product information
  - Analog guest room phone HD340A + Corded handset | gunmetal black | PN 00007045
- Equipment
  - Anti-bacterial housing
  - Sturdy, solid construction
  - [Fully customisable faceplate for hotel branding and dialing instructions<sup>1</sup>](#)
- Placement: Indoor, desktop, nightstand, wall mounting

## Dimensions and weight

- Dimensions (H × W × D, approx.)
  - Corded handset (on the base cradle, desk mounted): 183 mm × 82 mm × 121 mm
  - Corded handset (on the base cradle, wall mounted): 216 mm × 82 mm × 61 mm
  - Packaging (1 × HD340A): 214 mm × 152 mm × 110 mm
  - Packaging (12 × HD340A): 234 mm × 480 mm × 460 mm
- Weight (approx.)
  - Corded handset (on the base cradle, desk mounted): 544 g
  - Corded handset (on the base cradle, wall mounted): 363 g
  - Packaging (12 × HD340A): 10.67 kg

## Indicators and keys

- Telephone base: 3 LED indicators
  - Call status indication | Message waiting indication (MWI): 1 red LED
  - Mute status indication: 1 red LED
  - Speakerphone mode: 1 red LED

- Telephone base: 23 hard keys in total
  - 12 keys (standard ITU telephone keypad)
  - 4 dedicated audio keys
    - Mute (with red LED)
    - Speakerphone mode (with red LED)
    - *VOL+* → Volume +
    - *VOL-* → Volume -
  - 5 programmable function keys: Speed dialling
  - 2 dedicated function keys: *PROGRAM* + *PAUSE*
- 2 switches
  - Ringer tone selection switch
  - 4 jumpers: Voicemail voltage detection

## Audio devices and features

- Telephone base
  - Casing microphone
  - Casing speaker
- Corded handset
  - Microphone
  - Handset earpiece
- Hearing aid compatible (HAC)

## Interfaces and connections

- Wired interfaces
  - Telephone base
    - Network connectivity (PABX): RJ11-6P4C socket
    - Handset cord: custom socket
  - Corded handset
    - Handset cord: custom socket

## Call features

- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- [Multicast paging](#)

## Environmental conditions

- Operating ambient temperature
  - 5 °C - +45 °C
- Humidity (non-condensing)
  - 5 % - 95 %

## Package contents

- Hardware
  - Telephone base

- Handset
- Handset cord: 330 mm
- Telephone line cord: 2 m
- Footstand
- Wall mount kit
- Documentation
  - **Safety instructions (GPSR)**

## Series overview



## Disclaimer

[Further information: Snom HD340A webpage](#) | [Snom Service Hub HD340A](#) | [Safety instructions HD340A](#) | [Short User Manual HD340A](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.