

HD341A



Hotel/hospitality features



DECT handset



Anti-bacterial housing



HD audio

Analogue DECT telephone for hotels and guest areas

The HD341A is an analogue telephone for those who value the essentials without sacrificing convenience. With just two rows of keys and a clear operating structure, it offers all the essential functions: five speed dial keys for hotel facilities, a speakerphone function, volume control, and mute. The slim phone is equipped

with a DECT base station, allowing for greater freedom of movement. Thanks to the interchangeable receiver faceplate and custom-designed inserts, this slim desk phone blends perfectly into any environment.

Basics and equipment

- Product information
 - Analog guest room phone HD341A + Cordless handset | gunmetal black and black | PN 00007043
 - Anti-bacterial housing
 - Sturdy, solid construction
 - [Fully customisable faceplate for hotel branding and dialing instructions](#)
- Placement: Indoor, desktop, nightstand, wall mounting

Dimensions and weight

- Dimensions (H × W × D, approx.)
 - Cordless handset (on the base cradle, desk mounted): 183 mm × 82 mm × 121 mm
 - Cordless handset (on the base cradle, wall mounted): 216 mm × 82 mm × 61 mm
 - Packaging (1 × HD341A): 214 mm × 152 mm × 110 mm
 - Packaging (12 × HD341A): 234 mm × 480 mm × 460 mm
- Weight (approx.)
 - Cordless handset (on the base cradle, desk mounted): 499 g
 - Cordless handset (on the base cradle, wall mounted): 318 g
 - Packaging (12 × HD341A): 10.67 kg

Indicators and keys

- Cordless handset: 7 LED indicators
 - Call status indication | Message waiting indication (MWI): 1 red LED
 - Flash/Talk key indication: 1 green LED

- Mute status indication: 1 red LED
- MWI key: 1 red LED
- Hold status indication: 1 red LED
- Speakerphone mode: 1 red LED
- Low battery indication: 1 red LED
- Telephone base: 5 LED indicators
 - Call status indication | Message waiting indication (MWI): 1 red LED
 - Speakerphone mode: 1 red LED
 - Charging indication: 1 red LED
 - Mute status indication: 1 red LED
 - Low battery indication: 1 red LED
- Cordless handset: 23 hard keys in total
 - 12 keys (standard ITU telephone keypad), backlit
 - 4 dedicated audio keys
 - Speakerphone (with red LED)
 - Mute (with red LED)
 - Volume + / - (rocker)
 - 3 programmable function keys: Speed dialling
 - 4 dedicated function keys
 - Offhook (with red LED)
 - Onhook / Cancel
 - Hold (with red LED)
 - Message
- Telephone base: 27 hard keys in total
 - 12 keys (standard ITU telephone keypad)
 - 4 dedicated audio keys
 - Speakerphone (with red LED)
 - *MUTE* → Mute (with red LED)
 - *VOL+* → Volume +
 - *VOL-* → Volume -
 - 5 programmable function keys: Speed dialling
 - 1 dedicated function key: Handset localisation

Interfaces and connections

- Telephone base: Power options
 - Power adapter: 6 V
- Cordless handset: Power options
 - Battery (CORUN) lithium-ion, 3.7 V, 1000 mAh, removable, rechargeable, up to 7 h talk time, up to 168 h standby time, up to 11 h charging time
- Telephone base: Wired interfaces
 - Power adapter: coaxial power connector (socket)
 - Network connectivity (PABX): RJ11-6P4C socket
- Telephone base: Wireless interfaces
 - Handsets: DECT

Audio devices and features

- Telephone base
 - Casing microphone
 - Casing speaker
- Cordless handset
 - Microphone
 - Handset earpiece
 - Speakerphone mode: External speaker
- Built-in assignable ringtones
- Hearing aid compatible (HAC)

DECT technology and features

- Standard: DECT
 - Handsets: up to 4 total
 - Wideband audio
- Frequency band
 - EU & UK & AU: 1,881.792 - 1,897.344 MHz
- Easy registration to compatible base stations

Call features

- Quick call answer (by simple pick-up from the base/charger)

- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Speakerphone mode (via dedicated function key)
- Hold (via dedicated function key)

Environmental conditions

- Operating ambient temperature
 - 5 °C - +45 °C
- Humidity (non-condensing):
 - 5 % - 95 %

Package contents

- Hardware
 - Telephone base
 - Power adapter
 - Footstand
 - Wall mount kit
 - Cordless handset
 - Battery
- Documentation
 - **Safety instructions (GPSR)**

Snom accessories and compatible devices

- PoE injector
 - **A5E (PN 00004679)**
- Power adapter
 - EU: Base PSU (PN 00004687)
 - UK: Base PSU (PN 00004688)
 - AU: Base PSU (PN 00004689)
- Battery PN 00004627
- DECT handset & charging cradle
 - Up to 3 × **HD3 (PN 00007011)**

Series overview



HD3



HD30L /
HD30LA



HD300 /
HD300A



HD331 /
HD331A



HD340 /
HD340A



HD341 /
HD341A



HD350W /
HD350A



HD351W /
HD351A

¹ Available separately

Disclaimer

[Further information: Snom HD341A webpage](#) | [Snom Service Hub HD341A](#) | [Short User Manual HD341A](#) | [Safety instructions HD341A](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.