

HD350A



Hotel/hospitality features



Customisable faceplate



Anti-bacterial housing

Elegant analog guest phone for the hotel/hospitality sector

The Snom HD350A is a well-designed corded analog guest room telephone.

The antibacterial housing to protect against germs is a real plus in everyday life. A clearly visible LED alerts the guest to calls or waiting messages. Customisation is done via faceplates. Wall or table

mounting is possible. The device is GDPR compliant by design: no data storage of personal information such as dialled phone numbers is carried out!

Basics and equipment

- Product information
 - Analog guest room phone | Corded handset | PN 00007030
 - Colour: gunmetal black
 - Anti-bacterial housing
- Equipment
 - Sturdy, solid construction
 - [Fully customisable faceplate for hotel branding and dialing instructions¹](#)
- Placement: indoor, desktop, nightstand, wall mounting

Dimensions and weight

- Dimensions (H × W × D, approx.)
 - Corded handset (on the base cradle, desk mounted): 109 mm × 146 mm × 182 mm
 - Corded handset (on the base cradle, wall mounted): 109 mm × 56 mm × 216 mm
- Weight (approx.)
 - Corded handset (on the base cradle): 778 g

Indicators and keys

- Telephone base: 3 LED indicators
 - Call status indication | Message waiting indication (MWI): 1 red LED
 - Mute status indication: 1 red LED
 - Speakerphone mode: 1 red LED
- Telephone base: 27 hard keys in total
 - 12 keys (standard ITU telephone keypad)
 - 4 dedicated audio keys
 - Mute (with red LED)
 - Speakerphone (with red LED)
 - Volume +
 - Volume -

- 10 programmable function keys: Speed dialling
- 1 dedicated function key: Hold

Audio devices and features

- Telephone base
 - Casing microphone
 - Casing speaker
- Corded handset
 - Microphone
 - Handset earpiece
 - Hearing aid compatible (HAC)

Interfaces and connections

- Wired interfaces
 - Telephone base
 - Network connectivity (PABX): RJ11-6P4C socket
 - Handset cord: custom socket
 - Corded handset
 - Handset cord: custom socket

Environmental conditions

- Operating ambient temperature:
 - 5 °C - +45 °C
- Humidity (non-condensing):
 - 5 % - 95 %

Package contents

- Hardware
 - Telephone base
 - Corded handset: Cable length (approx.) 0.3 m
 - Footstand
 - Wall mount kit
- Documentation
 - [Quick Installation Guide](#)

Series overview



HD300²



HD30L²



HD331²



HD350W²



HD351W²



HD3

¹ Available separately

² Also available as analogue model

Disclaimer

Further information: [Snom HD350A webpage](#) | [Snom Service Hub](#) | [User manual](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.