

HD351A











Customisable faceplate



Anti-bacterial housing



HD audio

Elegant analog guest phone with wireless DECT handset for the hotel/hospitality sector

The Snom HD351A is a well-designed analog cordless guest room telephone.

The antibacterial housing to protect against germs is a real plus in everyday life. A clearly visible LED alerts the guest to calls or waiting messages. Customisation is done via faceplates. Wall or table mounting is possible. The device is GDPR compliant by design: no data storage of personal information such as dialled phone numbers is carried out!

Technical specification



Basics and equipment

- Product information
 - Analog guest room phone | Cordless DECT handset | PN 00007031
 - Colour: gunmetal black
 - Anti-bacterial housing
- Equipment
 - Sturdy, solid construction
 - Telephone base: Fully customisable faceplate for hotel branding and dialing instructions¹
 - Cordless DECT handset: Customisable section for colour or hotel branding¹
- Placement: indoor, desktop, nightstand, wall mounting

Dimensions and weight

- Dimensions (H × W × D, approx.)
 - Cordless DECT handset (on the base cradle, desk mounted): 109 mm × 146 mm × 182 mm
 - Cordless DECT handset (on the base cradle, wall mounted): 109 mm × 56 mm × 216 mm
- Weight (approx.)
 - Cordless DECT handset (on the base cradle):
 796 g

Keys

- 50 hard keys in total
- Telephone base
 - 12 keys (standard ITU telephone keypad)
 - 4 dedicated audio keys
 - Mute (with red LED)
 - Speakerphone (with red LED)
 - Volume +
 - Volume -
 - 3 dedicated function keys
 - Message
 - Hold
 - Emergency
 - 8 programmable function keys
 - Speed dialling

- Cordless DECT handset
 - 12 keys (standard ITU telephone keypad), backlit
 - 4 dedicated audio keys
 - Mute (with red LED)
 - Speakerphone (with red LED)
 - Volume +
 - Volume -
 - 3 programmable function keys
 - Speed dialling
 - 4 dedicated function keys
 - Talk (with green LED)
 - Off
 - Message
 - Hold

Technical specification



Indicators

- 9 LED indicators
- Telephone base
 - Call status indication | Message waiting indication (MWI): 1 red LED
 - Mute status indication: 1 red LED
 - Speakerphone mode: 1 red LED
 - Charging indication: 1 red LED
- Cordless DECT handset
 - Message waiting indication (MWI): 1 red LED
 - Flash/Talk key indication: 1 green LED
 - Speakerphone mode: 1 red LED
 - Mute status indication: 1 red LED
 - Low battery indication: 1 red LED

Interfaces and connections

- Power options
 - Telephone base
 - Power adapter
 - 100 240 V AC / 50 60 Hz / 500 mA | 5 V DC / 2 A
 - Cordless DECT handset
 - Battery lithium-ion, 3.7 V, 1,000 mAh, removable, rechargeable, up to 7 h talk time, up to 144 h standby time
- Wired interfaces
 - Network connectivity (PABX): RJ11-6P2C socket
 - Power adapter: coaxial power connector (socket)
- Wireless interfaces
 - Handset: DECT³

Audio devices and features

- Telephone base
 - Casing microphone
 - Casing speaker
- Cordless DECT handset
 - Microphone
 - Handset earpiece

• Hearing aid compatible (HAC)

DECT technology and features

- Standard: DECT³
 - Handsets: up to 4 total
 - Wideband audio
- Frequency band
 - EU & UK: 1,881.792 1,897.344 MHz
- Easy registration to compatible base stations

Call features

- Quick call answer (by simple pick-up from the base/charger)
- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- Speakerphone mode (via dedicated function key)
- Hold (via dedicated function key)



Environmental conditions

- Operating ambient temperature:
 - 5 °C +45 °C
- Humidity (non-condensing):
 - 5 % 95 %

Package contents

- Hardware
 - Telephone base
 - Cordless DECT handset
 - Batterv
 - Power adapter
 - Footstand

- Wall mount kit
- Documentation
 - Quick Installation Guide

Snom accessories and compatible devices

- DECT handset & charging cradle
 - Up to 3 × HD3 (PN 00007011)
- Battery PN 00004627
- Power adapter: HD351A PSU
 - EU: PN 00007036
 - UK: PN 00007037
 - AU: PN 00007038

Series overview









HD101



HD1







HD350W²



HD351W²



HM201

Disclaimer

Further information: Snom HD351A webpage | Snom Service Hub | User manual | Type approval | Warranty information | Company locations

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.

Available separately
 Also available as analogue model

 $^{^{3}}$ DECT devices manufactured for the USA and Canada are marketed as DECT 6.0