

M100 SC



DECT



Single-cell system



GAP compatible



Shared Call Emulation (SCE)



Power over Ethernet (PoE)



Security (TLS & SRTP)



Directory



OTA Updates

The compact DECT base station for up to 8 SIP accounts

Up to 10 compatible M10 SC DECT handsets can be operated on the single-cell M100 SC base station, making the system ideal for small office/home office use. The unique Snom 'Shared Call Emulation' feature enables call sharing on all connected M10 SC handsets without programming knowledge or support from VoIP providers. The system can be set-up and maintained

both via the web interface and automatically through provisioning. Software updates of the M10 SC are carried out via the DECT interface of the base station, ensuring trouble-free operation at all times. Existing PoE switches can be used to power the base station via the network cable.

Basics

- Product information
 - **DECT single-cell base station M100 SC** | black | PN 00004451
 - Availability: Bundle Snom M110 SC (Snom M10 SC / Snom M100 SC), EU & UK, PN 00004610
- Placement: Indoor, desktop, wall mounting

Dimensions and weight

- Dimensions (H × W × D, approx.)
 - 151 mm × 116 mm × 42 mm
- Weight (approx.)
 - 227 g

Indicators and keys

- 2 LED indicators
 - Power status indication: **1** green LED
 - VoIP status indication: **1** green LED
- 2 hard keys in total
 - Handset localisation, Reset

Audio features

- Audio codecs: G.711 (A-law, μ -law), G.722, G.726, G.729AB, iLBC

Interfaces and connections

- Power options
 - **Power over Ethernet (PoE)**
 - IEEE 802.3af, class 2
 - Power adapter³
 - 100 - 240 V AC / 50 - 60 Hz | 5 V DC / 800 mA
- Wired interfaces
 - Ethernet 10/100 Mbit/s: RJ45-8P8C socket
 - Power adapter:³ coaxial power connector (socket)

- Wireless interfaces
 - DECT

User interfaces and setup

- **Configuration and setup via menu-driven web user interface (WUI)**
 - Password-protected login
 - Secure web server/client (HTTPS)
- **Automatic configuration via provisioning**
 - Loading of settings and firmware via HTTP, HTTPS, TFTP
 - **Secure Redirection And Provisioning Service (SRAPS) support**
 - Supported DHCP provisioning options 66, 159, 160
 - Secure provisioning with preinstalled certificate
 - **Remote management via TR-069**
 - Plug & Play (PnP) support
 - Provisioning file with AES encryption
- Customisation
 - Custom default file
- Localisation
 - **Languages**
 - Time zone, dial tone
- Diagnostic
 - PCAP trace, Syslog

DECT technology and features

- Standard: DECT
- Frequency band
 - Europe: 1,880 - 1,900 MHz
- Coverage
 - Up to 300 m outdoor range
 - Up to 50 m indoor range
- Handsets: up to 10
- Software upgrade over the air (SUOTA)

Directory support and call features

- 8 identities / accounts
 - Up to 6 simultaneous calls
- Directory support
 - [LDAP \(server-based directory\)](#)
 - Import/export phone book (CSV, XML)
 - Central directory on the base station with up to 1,000 shared entries
 - [XML phonebook support](#)
- Outgoing call features
 - Speed dialling: up to 10
 - [Local dial plan](#)
 - [Redial](#)
 - Caller identification (CLIP)
 - Intercom between DECT handsets²
- Incoming call features
 - **Call barring / blocking:** deny list, anonymous calls, Do Not Disturb (DND) mode
 - [Call diversion](#)
- Connected call features
 - Mute microphone
 - Hold
 - [Blind call transfer](#)
 - [Attended call transfer](#)
 - External/internal call transfer between DECT handsets²
 - N-way network conferencing
 - 3-way (2+1) local conferencing
- Related features
 - Call history of 200 missed, received, dialed calls
 - Phone book matching for incoming and outgoing calls
 - Shared Call Emulation⁴
 - Call timer (call duration)

Networking technologies and protocols

- Network technologies
 - [VLAN \(IEEE 802.1q\)](#)

- [OpenVPN](#)
- VoIP related protocols and techniques
 - [SIP, RTP, STUN](#)
- Secure VoIP protocols
 - [SRTP](#)
- Network protocols
 - IPv4 /IPv6: Static, PPPoE, [DHCP](#), [LLDP-MED](#), HTTP, FTP, [TFTP](#), [SNTP](#), [NAT](#)
- Secure network protocols
 - [TLS V1.2](#), [HTTPS](#), [IEEE 802.1X \(p/q\)](#)
- Quality of Service (QoS)
 - ToS, DiffServ
- Remote management protocols
 - [TR-069](#)
- Related features
 - DNS Override
 - Mutual authentication
 - Failover support and server redundancy

Environmental conditions

- Operating ambient temperature: 0 °C - +40 °C
- Humidity (non-condensing): < 95 %

Package contents

- DECT base station M100SC
- Ethernet cable
- Wall mount plate
- [Quick Installation Guide](#)

Snom accessories and compatible devices

- PoE injector
 - [A5E \(PN 00004679\)](#)
- Power adapter
 - EU: M100 PSU (PN 00004373)
 - UK: M100 PSU (PN 00004374)
- DECT handset:
 - [M10 SC \(PN 00004452\)](#)
- Bundle
 - [M110 SC Bundle \(PN 00004610\)](#)

Interoperability



¹ Features and functionality may vary, depending on SIP service provider and/or SIP phone system platform

² Function only available when paired to the M10 SC

³ Available separately

⁴ Shared Call Emulation: Snom's unique PBX feature emulation for line, hold/unhold and call pick-up

Series overview



M110 SC



M100 SC



M10 SC

Disclaimer

[Further information: M100 SC webpage](#) | [Snom Service Hub M100 SC](#) | [Quick Installation Guide M100SC](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.