

M400



DECT



Single-cell
system



Power over
Ethernet (PoE)



Security (TLS &
SRTP)



OTA Updates



Directory

M400 - Base station for seamless business mobility

The single-cell M400 DECT base station offers the full range of telephony business features. The base station allows to manage up to 10 parallel calls with up to 20 SIP accounts. For Cloud and VoIP PBX partners, the M400 offers remote maintainability and

zero-touch deployment. The M400 complies with the latest encryption standards and shares the same architecture as the M900 multicell system for the latest software and security updates.

Product variants



M400 | EU & UK | PN
00004587



M400 | Americas | PN
00004588



M430 | EU | PN
00004589



M430 | UK | PN
00004590

Basics

- Product information
 - DECT single-cell base station
 - Colour: white
- Placement: indoor, desktop, wall mounting
- Antenna diversity: 2 internal omni-directional antennas

Dimensions and weight

- Dimensions (H x W x D, approx.)
 - 112 mm x 90 mm x 36 mm
- Weight (approx.)
 - 170 g

Indicators and keys

- Multi-purpose status indication: 1 multicolour LED
- 1 dedicated function key: Reset

Audio codecs and features

- Audio codecs: G.711 (A-law, μ -law), G.722, G.726, G.729
- Codec negotiation
- Codec switching

Interfaces and connections

- M400 power options
 - [Power over Ethernet \(PoE\)](#)
 - IEEE 802.3af, class 2
 - Power adapter¹
 - 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 2 A, 10 W

- Wired interfaces
 - Power adapter: coaxial power connector (socket)
 - Ethernet 10/100 Mbit/s: RJ45-8P8C socket
- Wireless interfaces
 - DECT²

User interfaces and setup

- [Configuration and setup via menu-driven web user interface \(WUI\)](#)
- [Automatic configuration via provisioning](#)
 - Loading of settings and firmware via HTTP / HTTPS / TFTP
 - Secure provisioning with preinstalled certificate
 - Cloud Zero-Touch Provisioning
- Localization
 - [Languages](#)
 - Timezone, dial tone
- Diagnostic
 - DECT messages, alarms, location
 - List of registered mobile handsets, repeaters, location gateways
- Related features
 - XML Minibrowser support for Snom DECT multicell systems
 - Compatible handset feature RSSI tool, no additional measurement equipment needed

Directory support

- Local directory with up to 3,000 entries
- LDAP (server-based directory)
- XML phonebook support

DECT technology and features

- Standard: DECT²
 - Authentication/encryption of base and handset
 - Seamless handover
 - Wideband audio
- Frequency band
 - Europe: 1,880 - 1,900 MHz
 - USA: 1,920 - 1,930 MHz
 - Latin America: 1,910 - 1,930 MHz
- Output power
 - Europe: < 250 mW
 - USA: < 100 mW
 - Level (dbm): 14, 17, 20, 24
- Coverage
 - Up to 50 m indoor range
 - Up to 300 m outdoor range
- Single-cell installation
 - Handsets: up to 20
 - Repeaters: up to 6
 - Narrowband calls: up to 10
 - Wideband calls: up to 5
- Software upgrade over the air (SUOTA)

Networking technologies and protocols

- Network technologies
 - VLAN (IEEE 802.1Q)
- Secure VoIP protocols

- SIPS (SIP over TLS), SRTP (RFC 3711)
- Network protocols
 - DHCP, NTP, LLDP-MED, HTTP
- Secure network protocols
 - TLS V1.2, HTTPS
- Quality of Service (QoS)
 - ToS

Environmental conditions

- Operating ambient temperature: -10 °C - 50 °C

Package contents

- Hardware
 - DECT base station M400
- Documentation
 - Quick Installation Guide (QIG)
 - Information sheets (security, standards)

Interoperability

- Certified VoIP partner

Snom accessories and compatible devices

- Power adapter: Snom 10W PSU
 - EU & UK (PN 00004570)
 - Americas (PN 00004571)
- DECT repeater
 - M6 (PN 00004638, PN 00004639, PN 00004640)
- Compatibility
 - Please check compatibility list

¹ If PoE is not available

² DECT devices manufactured for the USA and Canada are marketed as DECT 6.0

Series overview



M25



M30



M65 (EoS)



M70



M80



M85



M90



M400



M700 (EoL)



M900



M900 Outdoor



M6



M9B



M9T

Disclaimer

Further information: [Snom website](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#)

Snom is a registered trademark of Snom Technology GmbH in the European Union, USA, Japan, China and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, are legally protected trademarks of Snom Technology GmbH. Other mentioned trademarks or registered trademarks are the property of their respective manufacturers or owners. Product specifications are subject to change without notice. We do not accept liability for printing errors and mistakes.