

SP800



USB port



HD audio



Security (TLS & SRTP)



OpenVPN

The perfect solution for anyone who has to make calls without a phone

Snom SP800 (without display or keypad) is the ideal solution for businesses that want to securely connect their employees via remote desktop or soft client to the cloud without compromising on perfect audio quality. Equipped with the features of a D862 desk phone, the SP800 guarantees the familiar first-class

Snom audio experience for users without compromising on security. Even in the most demanding scenarios, voice transmission remains clear and understandable.

Basics

- Product information
 - IP desk phone terminal | gunmetal black | PN 00004641
 - Operating system: Linux
- Placement
 - indoor, wall mounting¹

Dimensions and weight

- Dimensions (L × W × H, approx.)
 - 110 mm × 110 mm × 30.2 mm
- Weight (approx.)
 - 145 g

Indicators and keys

- 2 LED indicators
 - Call status indication: 1 green LED
 - Power status indication: 1 red LED
- 1 dedicated function key: Reset

Audio devices, codecs and features

- Audio codecs
 - G.711 (A-law, μ -law), G.722, G.723.1, G.726, G.729, Opus
- Dual-tone multi-frequency signalling (DTMF / RFC2833):
 - SIP-INFO, in-band, out-of-band
- Related features
 - Comfort Noise Generator (CNG)
 - Voice Activity Detection (VAD)
 - Audio response time
 - Adaptive jitter buffer
 - Packet loss concealment (PLC)

Interfaces and connections

- Power options
 - [Power over Ethernet \(PoE\)](#)
 - IEEE 802.3af, class 3 | IEEE 802.3az⁴

- Power adapter¹
 - 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 2 A, 10 W¹
- Wired interfaces
 - Power adapter: coaxial power connector (socket)
 - Network connectivity: 2 × RJ45-8P8C (PC/NET) sockets → Gigabit Ethernet (GbE)
 - [USB headsets and other accessories](#):³ 2 × USB 2.0 type A ports
 - Headset: 3.5 mm miniature audio jack
 - Maintenance (Snom): RJ12-6P6C (EHS) socket

User interfaces and setup

- [Configuration and setup via menu-driven web user interface \(WUI\)](#)
 - Visual and functional UX based re-design (phone manager)
 - Password-protected login
 - Secure web server/client (HTTPS)
- [Computer telephony integration \(CTI\)](#)
 - [uaCSTA over SIP, CSTA over HTTP\(S\)](#)
- [Automatic configuration via provisioning](#)
 - Loading of settings and firmware via HTTP, HTTPS, TFTP
 - Supported DHCP provisioning options 43 / 60 / 66 / 67
 - [Secure Redirection And Provisioning Service \(SRAPS\) support](#)
 - [Remote management via TR-069 / TR-069 Annex G \(TR-111\) / TR-369](#)
 - Plug & Play (PnP) support
- Localization
 - [Languages](#)
 - Time zone, dial tone
- Diagnostic
 - SIP / PCAP trace
 - Syslog

Networking technologies and protocols

- Network technologies
 - [OpenVPN](#), [VLAN \(IEEE 802.1q\)](#)
- VoIP related protocols and techniques
 - [SIP](#), [SDP](#), [RTP](#), [RTCP](#), [RTCP-XR](#), [SIP REFER](#) method ([RFC 3515](#)), [rport \(RFC 3581\)](#), [ENUM](#), [ICE](#), [STUN](#)
- Secure VoIP protocols
 - [SIPS \(SIP over TLS\)](#), [SRTP](#), [SRTCP](#)
- Network protocols
 - [IPv4 / IPv6 \(dual stack\)](#), [DHCP](#), [NTP](#), [LDAP](#), [LLDP-MED](#), [HTTP](#), [TFTP](#), [L2TP](#)
- Secure network protocols
 - [TLS V1.3](#) incl. ciphers (forward secret & authenticated), [HTTPS](#), [IEEE 802.1X \(EAP-TLS - RFC 5216\)](#)
- Remote management protocols
 - [TR-069](#), [TR-069 Annex G \(formerly TR-111\)](#), [TR-369 \(USP\)](#), [uaCSTA over SIP](#), [CSTA over HTTP\(S\)](#)

Directory support and call features

- 8 identities / accounts
- Directory support
 - [LDAP \(server-based directory\)](#)
 - [Local directory with up to 10,000 entries](#)
 - [Import/export phone book \(CSV, XML\)](#)
- Outgoing call features
 - [URL dialling](#)
 - [Local dial plan](#)
 - [Automatic redial on busy](#)
 - [Caller identification \(CLIP\)](#)
 - [Calling Line Identification Restriction \(CLIR\)](#)

- [Call completion \(busy/unreachable\)²](#)
- Incoming call features
 - [Call waiting/swapping](#)
 - [Auto answer](#)
 - [Call diversion](#)
 - [Call barring/blocking: deny list, dynamic central blacklist check²](#), [anonymous calls](#)

Interoperability

- [Certified VoIP partner](#)

Environmental conditions

- [Operating ambient temperature: 0 °C - +35 °C](#)
- [Nonoperating \(storage\) temperature: -10 °C - +45 °C](#)
- [Humidity \(non-condensing\): 5 % - 95 %](#)

Package contents

- Hardware
 - [IP desk phone terminal SP800](#)
 - [Ethernet cable: 1.5 m](#)
- Documentation
 - [Quick Installation Guide](#)

Snom accessories and compatible devices

- Power adapter
 - [Snom 10 W PSU \(PN 00004570\)](#)
- Wall mount kit
 - [SP800 \(PN 00004657\)](#)
- Wired headset via USB
 - Binaural: [A330D \(PN 00004598\)](#)
 - Monaural: [A330M \(PN 00004597\)](#)
- Wireless conference speakerphone (USB)
 - [C300 \(PN 00004584\)](#)



10 W PSU



A330D



A330M



C300

¹ Available separately

² If supported by PBX

³ Please check compatibility list

⁴ Optional via software

Series overview



PA1+



SP800

Disclaimer

Further information: [Snom SP800 webpage](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.