

## V420




Ideal for video-telephony



USB port



Plug & Play



Snom Connect Desktop

### Professional video quality for your meetings

The Snom V420 webcam combines razor-sharp 4K image quality with intelligent audio technology, making it the ideal solution for professional video conferencing, live streams, and high-quality recordings. Thanks to automatic exposure adjustment and variable viewing angle adjustment, it delivers a brilliant image even in difficult lighting conditions – whether in the home office

or in a conference room. Three integrated microphones ensure clear voice transmission: two omnidirectional (left and right) and one unidirectional (center) for precise beamforming. With a frequency range of 20 Hz to 10.0 kHz, a sensitivity of -38 dB, and a range of up to 5 meters, the V420 is also acoustically well-equipped.

## Basics and equipment

- Product information
  - Video conference camera (4K) | gunmetal black | PN 00004723
- Equipment
  - Camera with adjustable FOV
  - Beamforming microphone array
  - Convenient mounting

## Dimensions and weight

- Dimensions (D x W x H, approx.)
  - Packaging: 126 mm x 131 mm x 86 mm
  - Camera: 81 mm x 56 mm x 57 mm
- Cable length (approx.)
  - 2.2 m
- Weight (approx.)
  - Camera: 139.5 g

## Indicators

- Multi-purpose status indication: 1 LED indicator ( green, orange, red )

## Video camera features

- Image sensor: CMOS (APS), 1/2.7" (4:3 → 5.33 mm x 4.0 mm, diagonal 6.7 mm), 8 Megapixel (MP)
- Resolution / Frame rate / USB:
  - 4K @ 30 FPS (USB 3.0)
  - 1080p @ 30 FPS (USB 2.0)
  - 720p @ 30 FPS
- Field of view (FOV):<sup>1</sup>
  - Horizontal: 87° - 110°
  - Vertical: 54° - 72°
  - Diagonal: 95° - 120°
- Aperture: f/2.4
- Depth of field (DOF): 0.5 m - 3 m

## Audio features

- 3 microphones
- Omnidirectional (left, right) and unidirectional (middle) for beamforming
- Frequency range: 20 Hz - 10.0 kHz
- Sensitivity: -38 dB
- Pickup range: up to 5 m

## User interfaces and setup

- PC (≥ Windows 10) / Mac (≥ macOS 12.0): [Snom Connect Desktop App](#)

## Interfaces and connections

- Power options
  - USB powering: 5 V
- Wired interfaces
  - USB 3.0 type C port

## Interoperability

- Communication software platforms (PC/Mac): Zoom, MS Teams, Webex, Google Meet

## Environmental conditions

- Operating ambient temperature
  - 5 °C - +35 °C
- Nonoperating (storage) temperature
  - -20 °C - +60 °C

## Package contents

- Hardware
  - Video conference camera
  - 1 x 2.2 m USB-C to USB-A cable
- Documentation
  - [Quick Installation Guide](#)

<sup>1</sup> Configuration via the [Snom Connect Desktop app](#)

## Series overview



A5E



10W PSU



A210



A230



ACPJ



ACPJ25



ACUSB



HD3xx design  
handset cover



WM D120



EHS 2.0



MC10



DECT Measuring  
Kit



V420

## Disclaimer

[Further information: Snom V420 webpage](#) | [Snom Service Hub V420](#) | [Quick Installation Guide V420](#) | [Snom Connect Desktop App](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.